

# **GFK Unlimited 2018**

10. Internationale Tagung

6. – 7. Februar 2018, München

**Ashland Technologies GmbH**

**Michael Jäger**

**&**

**Plasticon Composites International Contracting BV**

**Gunar Krause**

High temperature resins and their use in hot flue gas applications


- Companies
- Materials and High Temperature Resistant (HT) Resin
- Case Studies
- Engineering and Fabrication

## Introducing Plasticon Composites


- Headquarter in NL, founded in 1952.
- Worldwide presence, production facilities and sales all over the world.
- More than 700 employees in 16 Production Locations with approx. 80.000 m<sup>2</sup> size in 13 countries.
- Approx. 1.500.000 hours production capacity per year.
- Capability of 200.000 h/a to do Installation projects.
- 15 stationary and 5 onsite winding machines.




- Headquartered in Covington, Kentucky, founded 1924
- Specialty Chemicals, sales in over 100 countries
- 6000 Employees, 1100 in Composites
- 41 Production Plants, 16 for Composite Resins
- Revenue: \$3.2bn, \$770M in Composites



## Composite Resin Plants



- Fluegases and their condensates etc. can be very corrosive (Chlorides...)
- FRP can even outperform exotic materials such as high nickel alloys
- FRP is cost competitive with stainless steel



HT Novolak Epoxy Vinyl Ester Resin successfully used since 25 years in Quenches, Scrubbers, Ducts and Chimneys







- ✓ Physical Properties
- ✓ Thermal shock and cycling
- Thermal ageing
- Upset performance testing

- ✓ Field Experience:  
E.g. Quench with brick  
lining failure exposing  
the FRP structure to  
260°C for > 1 year.


**Excellent Emergency  
Running Properties!**



- Not insulated: Max. continuous Fluegas Temperature: ~230°C
- Insulated: Max. continuous Fluegas Temperature: ~200°C





3mm VE-HT resin Laminate after 12 months at 200°C: Approx. 0.25mm of the surface is oxidised, the core looks like new!





Approx. 3mm












Weight retention of 10mm laminate in air at 330°C  
(One side exposed, insulated, C- vs Carbon-veil, Carbon CSM, and Graphite)






- “Waste To Energy” Plant, HVC Alkmaar/NL, 1995
- 1 million tons of waste per year
- 4 trains with FRP quench and scrubber



### Fluegas Treatment System, HVC Alkmaar:

- 4 Quenches, HT resin, designed for max. 230°C
- 4 Scrubbers, two-stage (acid/alkaline), VE resin, designed for 90°C



### Quench History:

- Flue gas with HCl, HF, SO<sub>2</sub>, SO<sub>3</sub>, NO<sub>x</sub>, dust.
- Service time 1<sup>st</sup> unit: 1995 – 2008 (average service life = 13 years)
- CR Liner renovation every ~3 years



### Quench CR Liner before and after renovation





- FRP based on “HT” resin outperforms conventional materials in hot flue gas applications since 25 years
- The Alkmaar HVC WTE plant is in operation since over 20 years and confirms the superior performance of quenches based on HT resin in flue gas cleaning.
- Data for short and medium term upset conditions have been generated. While several weeks of operation appear feasible at 230°C (insulated), it seems reasonable to limit excursions to 330°C to max. 30 min, followed by an inspection. Higher temperatures are not considered.
- Fillers like e.g. graphite may have a detrimental effect above 300°C. This needs to be further studied.



Chimney Liner



Ducts inside Cooling Tower



Chimneys



Ducts outside Cooling Tower



Storage Tanks



Absorber





Recirculation pipes




Spray header



Plasticon Composites always makes a detailed FEM analysis and assessment for the choice of the laminate (Combination and type of Resin and Glass) for major power plant components, to ensure reliability and long term performance of the product considering required loads and combination of loads:


- Medium
- Own weight
- Temperatures  
(Operating under FGD, Malfunction/Bypass)
- Pressure
- Seismic
- Ash load
- Snow load
- Wind
- Connected platforms






- Installation on concrete foundation, provided by the client.
- Air conditioned double wall tent.
- Winding wagon, movable on rails.
- Mould made of steel or carbon fibre.
- Length of the can 6 or 10 m, and diameter up to 21 m.
- Can  $\varnothing$  8 m and length of 6 m incl. stiffeners = 2 days production







- Assembly of single cans to modules incl. internals, pipes and attachments such as platforms and ladders to modules.
- Installation of the bottom made of board material.
- Installation of the modules with mobile cranes.
- Access to the seams with console scaffolds.





- Assembly of the transition piece and the lowest chimney can.
- Installation of the modules with a mobile crane.
- Access to the seams with console scaffolding.






- Assembly of 2 Cylinders in vertical Position.
- Assembly of in each step 2x2 Cylinders in horizontal Position, incl. internals, pipes and attachments such as platforms and ladders to modules.



- Installation of the modules with a mobile crane.
- Access to the outer seams with console scaffolds.
- Access to the internal seams with a mobile platform.



Project:	Cabot Project
Customer:	Babcock Wilcox
Product:	GRP Absorber including all internals, with self-supporting stack, and FRP holding tank.
Medium:	Clean Flue Gas
Year:	2017
Country:	United States of America
Description:	Turnkey incl. Engineering, Prefabrication, Transport, Lifting, Installation, Supervision and Quality control.

	Absorber	Stack	Aux. Tank
Dimensions:	Dia. 8,23 m Height 25,1 m	Dia. 3,8 m Level + 66,8 m	Dia. 8,23 m Height 11,2 m
Temperature:	82°C (255°C at Flue Gas Inlet)		77°C
Pressure:	-0.012 / 0.087 bar		-0.0254/0.0635bar





<b>Project:</b>	<b>Turow, Integration of WFGD</b>
<b>Customer:</b>	Babcock Noell GmbH
<b>Product:</b>	3 x Chimney liner & Bypass
<b>Dimensions:</b>	Dia. 5,3 m / Length 690 m
<b>Temperature:</b>	20°C to 163°C
<b>Pressure:</b>	-10 mbar / +20 mbar
<b>Medium:</b>	Clean Flue Gas
<b>Year:</b>	2014 / 2015
<b>Country:</b>	Poland
<b>Description:</b>	Engineering, Prefabrication, Installation, Supervision and Quality control.



Project:	Orot Rabin & Rutenberg
Customer:	CDI
Product:	4 x GRP liner in Concrete chimney
Dimensions:	Dia. 7.0 m / Height +210 m
Temperature:	52°C (150°C Excursion)
Pressure:	- 100 mbar / + 100 mbar
Medium:	Clean Flue Gas
Year:	2015 – 2016
Country:	Israel
Description:	Engineering, Prefabrication, Lifting, Jacking System, Installation, Supervision and Quality control



<b>Project:</b>	<b>Fort Martin; Stack liner</b>
<b>Customer:</b>	Karrena
<b>Product:</b>	1 x Stack liner
<b>Dimensions:</b>	Dia. 8.2 m – Height 125 m
<b>Temperature:</b>	65°C (190°C @ 4 hrs)
<b>Pressure:</b>	
<b>Medium:</b>	Clean Flue Gas
<b>Year:</b>	2008
<b>Country:</b>	USA; West Virginia
<b>Description:</b>	Turnkey incl. Engineering, Prefabrication, Transport, Lifting, Installation, Supervision and Quality control.





<b>Project:</b>	<b>KW Neurath BoA 2&amp;3</b>
<b>Customer:</b>	RWE Energie AG / GEA
<b>Product:</b>	2 x Flue gas duct Absorber to CT
<b>Dimensions:</b>	Dia. 10,0 m / Length 150m + 30m Elbow
<b>Temperature:</b>	-10°C to 73°C
<b>Pressure:</b>	-0,005 bar / +0,01 bar
<b>Medium:</b>	Clean Flue Gas
<b>Year:</b>	2007 / 2008
<b>Country:</b>	Germany
<b>Description:</b>	<p>Turnkey incl. Engineering, Prefabrication, Transport, Lifting, Installation, Supervision and Quality control. Project scope M€ 20</p> <p>We faced the challenge to construct a FRP duct of 10 m Ø at a support distance of 75 m.</p>




<b>Project:</b>	<b>PP Opole (PL); Clean gas ducts</b>
<b>Customer:</b>	Alstom Power Italia S.p.A
<b>Product:</b>	2 x Clean gas ducts
<b>Dimensions:</b>	Dia. 8,0 m / Length 65 m
<b>Temperature:</b>	52°C
<b>Pressure:</b>	-10 / + 10 mbar
<b>Medium:</b>	Clean Flue Gas
<b>Year:</b>	2012 / 2013
<b>Country:</b>	Netherlands
<b>Description:</b>	Turnkey incl. Engineering, Prefabrication, Transport, Lifting, Installation, Supervision and Quality control.





<b>Project:</b>	<b>Turow, Integration of WFGD</b>
<b>Customer:</b>	Babcock Noell GmbH
<b>Product:</b>	3 x Chimney liner & Bypass
<b>Dimensions:</b>	Dia. 5,3 m / Length 690 m
<b>Temperature:</b>	20°C to 163°C
<b>Pressure:</b>	-10 mbar / +20 mbar
<b>Medium:</b>	Clean Flue Gas
<b>Year:</b>	2014 / 2015
<b>Country:</b>	Poland
<b>Description:</b>	Engineering, Prefabrication, Installation, Supervision and Quality control.

**Thank you very much  
for your attention !**



The information contained in this presentation and the various products described are intended for use only by persons having technical skill and at their own discretion and risk after they have performed necessary technical investigations, tests and evaluations of the products and their uses. This material is for informational purposes only and describes the scientific support for the use of the products described herein as an ingredient intended to enhance performance of an end product. Certain end uses of these products may be regulated pursuant to rules governing medical devices or other regulations governing drug uses. It is the purchaser's responsibility to determine the applicability of such regulations to its products. While the information herein is believed to be reliable, we do not guarantee its accuracy and a purchaser must make its own determination of a product's suitability for purchaser's use, for the protection of the environment, and for the health and safety of its employees and the purchasers of its products.

Neither Ashland nor Plasticon nor their affiliates shall be responsible for the use of this information, or of any product, method, formulation, or apparatus described in this brochure. Nothing herein waives any of our conditions of sale, and no statement, information and data is to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which we assume legal responsibility. We also make no warranty against infringement of any patents by reason of purchaser's use of any information, product, method or apparatus described in this presentation.

The testing information (the "Testing Information") has been gratuitously provided by Ashland. The Testing Information is based on many factors beyond Ashland's control, including but not limited to, the conditions prevailing when the testing was conducted, and in some cases, is based on data generated with development samples of the Active Ingredient. Although it is intended to be accurate, ASHLAND DISCLAIMS ANY AND ALL LIABILITY, EITHER EXPRESS OR IMPLIED. You may not make commercial use of the Testing Information, or make claims with respect to your products based the Testing Information, without the written agreement with Ashland covering such use.

<sup>TM</sup> Trademark, Ashland or its subsidiaries, registered in various countries

\* Trademark owned by a third party